



AR400142

Remote fan unit 400 series

AR400142

- Powerful remote fan unit to combine with motorless appliances
 - Efficient BLDC technology
 - Air output according to EN 61591 - max. 880 m³/h.
 - Sound power level depends on the built-in situation.
 - Power levels depend on the motorless appliances
 - Powerful remote fan unit to combine with motorless appliances
- Efficient BLDC technology

Output

Air output according to EN 61591 - max. 880 m³/h.

Sound power level depends on the built-in situation.

Power levels depend on the motorless appliances

Features

3 electronically controlled power levels and one intensive mode.

Fan technology with highly efficient, brushless DC motor (BLDC).

Metal housing, zinc-plated.

Pipe connection pieces on intake side: 1 x NW 200 round, 4 x NW 150 round.

Pipe connection pieces on output side: 1x NW 150 round.

Spare cover for closing air intake.

Retaining bracket for installation on the ceiling or side of a cupboard enclosed.

Planning notes

Remote fan unit in combination with motorless appliances.

Connection to the respective appliances via network cable.

Installation in the plinth with cut-out for the air ducting in the furniture base.

When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.

Connection

Total connected load 240 W.

Connecting cable 1.8 m, pluggable.

Network cable 5 m.

